

VALVE TYPE		DIMENSION A	DIMENSION B	DIMENSION C
R2MH G3/8	DN 13MM	98	46	58
R2MH G1/2	DN 13MM	98	46	58
R2MH G3/4	DN 19MM	109	56	78
R2MH G1	DN 25MM	122	74	95



2/2 Serie R2MH Normally Closed


CODE	Connection	Orifice	Kv	Differential Pressure (bar)			Coil		Seal	Temp. Range
	G			Min	Max		Series	Width (mm)		
	ISO 228	mm	m³/h		AC	DC				
R2MHCCG#12///Coil	3/8"	13	2.2	0	10	10 (*)	3000	30	NBR=B EPDM=E FPM=V	-10 +90
					12	12	3600	36		
R2MHCDG#12///Coil	1/2"	13	2.5	0	10	10 (*)	3000	30		-10 +160
					12	12	3600	36		
R2MHCEG#18///Coil	3/4"	19	5,5	0	10	-	3000	30		-10 +160
					12	12	3600	36		
R2MHCFG#25///Coil	1"	25	10,2	0	10	6 (**)	3600	36		

: Please select the sealing type required
 Example: R2MHCCG#12///300E: ISO G1/2" NBR
 Coil 230V AC 15VA

(*) with coil 3C01
 (**) In case of use with ED >50% the nominal voltage tolerance to the coil has to be modified in +10% / -0%

Coils

SERIE	Coil P/N	Voltage	Nominal Power			Electrical connection	Connectors
			AC VA Inrush	AC VA Holding	DC Watt		
Series 3000 Width 30mm	3001	24V DC	-	-	10	DIN 43650A	On Demand
	3C01	24VDC	-	-	12		
	300B	24V AC	15	12	-		
	300E	230V AC	15	12	-		
Series 3600 Width 36mm	3601	24V DC	-	-	24		
	360B	24V AC	30	24	-		
	360E	230V AC	30	24	-		



DESCRIPTION

- Solenoid valve 2 ways, combined acting type.
- Brass body CW617N.

CONSTRUCTION


- Body: Brass CW614N
- Armature tube: Stainless steel Aisi 303
- Plunger and core: Stainless steel 430Fr
- Springs: Stainless steel Aisi 302
- Seal material: NBR - FPM - EPDM

FEATURES

- Maximum allowable pressure: 25bar*
- Maximum fluid viscosity: 25cSt (mm²/s)
- Ambient temperature:
with class F coil -10°C +55°C
with class H coil -10°C +80°C
- Above 80°C please consult our tech department for the application fine tuning
- Preferred mounting position with vertical coil above

OPTIONS

- Electroless nickel plating
- Version for vacuum application (air/gas)
- Others on request



SPARE PARTS

1. Coil fixing nut
2. Coil
3. Mobile plunger assembly
4. Armature tube kit
5. Diaphragm assembly